

Thermostats & Controls

101

TW Series

Features

- Single and double pole models
- Wire leads
- Tamper resistant
- Compliant with RoHS2 Directive (2011/65/EU), that of which includes the application exemptions outlined in Annex III of the directive
- Imported to TPI Corporation specifications

Load Rating

- 22 Amps resistive @ 120 VAC
- 18 Amps resistive @ 277 VAC



MFG CATALOG NUMBER	MFG MODEL NUMBER	DESCRIPTION	TEMPERATURE SCALE	LIST
05020002	TW145	SP, Beige with Leads	Tamper Resistant / 50-90°F	74
05020102	TW146	DP, Beige with Leads	Tamper Resistant / 50-90°F	87
Master Carton: 25 Pcs, 12 lbs. (varies slightly by model), 16" x 14" x 5.5"				

WARNING: This product can expose you to chemicals including nickel which is known to the State of California to cause cancer, and chromium, which is known to the State of California to cause birth defects and/or reproductive harm. For more information go to www.P65Warnings.ca.gov.

Washdown Series

Features

- Single and double pole models
- Rain tight NEMA 4X rating
- Stainless steel hardware
- Coil capillary temperature sensor
- Made in U.S.A. with domestic and foreign components

NEW PRODUCT for 2020



MFG CATALOG NUMBER	MFG MODEL NUMBER	DESCRIPTION	TEMPERATURE SCALE	CONNECTION	LIST
05234202	TW155A	SPDT Heat or Cool	40-110°F	6" Wire Leads	224
05234302	TW255A	DPDT Heat or Cool	40-110°F		260
22 Amps Resistive @ 120/250/277 VAC, 5" x 5" x 3" Case					

MFG CATALOG NUMBER	MFG MODEL NUMBER	DESCRIPTION	TEMPERATURE SCALE	CONNECTION	LIST
05234502	CTW155B	SPST Heat Only	40-110°F	6' Cord	239
05234602	CTW255C	SPST Cool Only	40-110°F		275
13 Amps @ 125 VAC Res. / 58.8 LRA @ 125 VAC / 9.8 FLA @ 125 VAC					

WARNING: This product can expose you to chemicals including nickel which is known to the State of California to cause cancer, and chromium, which is known to the State of California to cause birth defects and/or reproductive harm. For more information go to www.P65Warnings.ca.gov.



Industrial Series

Features

- Coil capillary (CKT) models
- Bi-Metal models (KT)
- Rugged steel case
- SPST & SDPT models
- Compliant with RoHS2 Directive (2011/65/EU), that of which includes the application exemptions outlined in Annex III of the directive. (KT models only)
- Hard wired models rated for 22A resistive @125-250 VAC
- Corded models rated for 13A resistive @125VAC
- Imported to TPI Corporation specifications



MFG CATALOG NUMBER	MFG MODEL NUMBER	DESCRIPTION	RANGE	CONNECTIONS	SCALE	LIST
05340402	CKTD110	SPDT Heat or Cool	40 - 110°F	Wire Leads	F	139
05340802	KT110	SPST Heat Only	-10 - 100°F	Wire Leads	C & F	59
05341002	KT121	SPST Heat Only	-10 - 100°F	6' Cord/Plug	C & F	65
05341702	KTD110	SPDT Heat or Cool	-10 - 100°F	Wire Leads	C & F	59
05343602	KTO110	SPST Cool Only	-10 - 100°F	Wire Leads	C & F	59
05342102	KTO121	SPST Cool Only	-10 - 100°F	6' Cord/Plug	C & F	65
Master Carton: 13.75" x 14" x 9", Qty 9-12, 14lbs.-16lbs. depending on model						



WARNING: This product can expose you to chemicals including nickel which is known to the State of California to cause cancer, and chromium, which is known to the State of California to cause birth defects and/or reproductive harm. For more information go to www.P65Warnings.ca.gov.