

Item # A71-DTCOVERLG, APO A71 DT COVER

List Price \$134.65



APO A71 DT COVER

ADTCOVER

Features

Vynckier Enclosure Systems' APO "DTCOVER" includes 5 sizes ranging from 12" x 7.5" to 12" x 24"
 The APO DT Cover is made of transparent polycarbonate and has a hinged transparent door for quick access. Set of two thumb screws are included.
 APO enclosures meet Ingress Protection standard IP67-11 and IP67-9 (NBN C20-001 annex A.)
 All bases are made of light gray (RAL7035) hot molded Fiberglass Reinforced Polyester (FRP).
 APO DT Covers are maintenance free and corrosion resistant.
 Vynckier's APO DT Covers are capable of withstanding continuous temperatures up to 248°F (120°C).
 APO DTCovers provide protection for equipment and operators from indirect electrical contact while allowing easy access.

Applications

Exclusive to Vynckier, the DT Cover is an accessory product that allows full view of instrumentation while protecting the system's monitors, pushbuttons, etc. The hinged transparent door allows full access to components and controls when needed, without constant exposure to the outside environment.

Standards

- IEC 439-1
- IEC 529 - Rated IP67-11
- EN 60439-1
- EN 60529
- CSA Certified per C22.2 No. 94

Approvals

- UL 508 NEMA 3, 3R, 4, 4X, 12 & 13
- CSA 3, 3R, 4, 4X, 12 & 13
- AS Australian Standards 3131-1991
- EExell, NIEB 88B.102.698 U
- LLOYD's Register of Shipping
- BASEEFA
- RoHS

SPECIFICATIONS

Availability	Standard Modified - 5 days
APO Outside Height (inch)	11.88
APO Outside Height (mm)	302
APO Outside Width (inch)	14.68
APO Outside Width (mm)	372
APO Outside Depth (mm)	45
APO Inside Height (inch)	10.25
APO Inside Height (mm)	260
APO Inside Width (inch)	11.60

APO Inside Width (mm)	294
APO Inside Depth (inch)	1.65
APO Inside Depth (mm)	42
APO Weight (lbs)	3.13
FRP UL Type Rating	3, 3R, 4, 4X, 12, 13
Temperature Resistance (F)	-58 to +248
Temperature Resistance (C)	-50 to +120