



**Description** 12V 20W 20 Deg. Medium Flood MR11 GU4 Base  
**Ordering Code** 15122  
**UNSPSC Code** 39101601

**Specifications**

|                                   |                    |
|-----------------------------------|--------------------|
| <b>Voltage Rating</b>             | 12                 |
| <b>Watts</b>                      | 20                 |
| <b>Amps</b>                       | 1.67               |
| <b>Base Type</b>                  | GU4                |
| <b>Bulb Type</b>                  | MR11               |
| <b>Filament</b>                   | C-8                |
| <b>MOL in/mm</b>                  | 1.38/35.0          |
| <b>MOD in/mm</b>                  | 1.39/35.3          |
| <b>Approx Initial Max Beam CP</b> | 1400               |
| <b>CT deg K</b>                   | 2900               |
| <b>Beam Angle</b>                 | 20                 |
| <b>Beam Description</b>           | Medium Flood       |
| <b>Rated Life</b>                 | 2,000              |
| <b>Common Code</b>                | Q20MR11/MFL        |
| <b>Burning Position</b>           | Any                |
| <b>Special Desc</b>               | Dichroic Reflector |
| <b>Type Use</b>                   | Display 20         |

watch > like > follow



selection. solutions. simplicity. [eiko.com](http://eiko.com)

23220 W. 84<sup>th</sup> St, Shawnee, KS 66227 · (P) 1.800.852.2217 (F) 1.800.492.8975

Canada: 81 King St, Barrie, ON L4N 6B5 · (P) 1.888.410.8151 (F) 1.888.705.1335