

MSDS LIST FOR NA PRODUCT

Model:FV-15NLFS1

ITEM	USED AT	FUNCTION	COMPONENT	RATIO
GRAIN ALCOHOL	All the Cleaning Process	Cleaning	Alcohol	100%
SRL LUBRICANT GREASE	Motor Assembling	Lubricate	Synthetic grease	100%
RUST VETO HEAVY	Motor Assembling	Rust prevention	Mineral oil	40%
			Paraffin	10%
			Solvent	5%
			Mahogany petroleum sulfonate	15%
			Composite antirust	20%
			Antioxidant	3%
			Preservative	7%
hydraulic oil Mobil DTE24#	For metal parts during punch process	Lubricate	hydrocarbon	97%
			chemical additive	3%
Volatile stainless steel scouring oil DS-S933	For metal parts during punch process	Lubricate	antirusting agent	2%
			lubricant	2%
			mineral oil	20%
			solvent	76%
GOOBER OIL	For metal parts during punch process	Lubricate	GOOBER OIL	100%
Nitro silver paint Q04-2	The frame welding process	Painting after welding	Nitro external enamel	90%
			Self-drying agent	7%
			Imported silver powder	3%
EA2	Shutter Assembling	Lubricate	Lubrication	80-90%
			Thicken Additive	10-20%
			Other Additive	2-7%
Metal ink	Print for lot number on name plate and Printing on carton box	Printing	Synthetic resin A	40%
			Synthetic resin B	40%
			Cellulose resin	20%
PAINT THINNER	Assembling Process	Assembling Assistance	Methyl Ethyl Ketone	10%-15%
			Butyle Acetate	5%-10%
			DDA	3%-5%
			N-Butyl Alcohol	25%-30%
			Acetic Ether	20%-30%
			Ethylene Glycol Monobutyl Ether	10%-15%
			Xylene	15%-20%