

## PVC Coated GUA Junction Boxes for Hazardous Locations - GUAX

Calbond GUA style fittings are available in a variety of shapes and dimensions. GUA style boxes are used in hazardous locations. All GUA style boxes are supplied PVC coated with PVC coated covers and a seal between the coating of the boxes and the coating of the covers.



### Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior Urethane coating thickness is a minimum 0.002"
- Sizes available are 1/2" to 2"
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes 1/2"- 2". For sizes 2-1/2"- 6", the length of the sleeve extension(s) shall be at least 2".

### Standards:

- National Electrical Code:
  - Class I, Div 1&2, Groups C,D
  - Class III
- UL Standard 886
- ANSI Standard C-33.27
- CSA Standard: C22.2 No. 30
- NEMA/EEMAC 3, 4

GUAX								
Item Number	Trade Size	Cover Opening	Weight Per 100 (lbs)	A	B	C	D	Aluminum Item Number
PV0500GUAX14	1/2"	2"	200	2.58	1.85	1.75	0.67	
PV0500GUAX16	1/2"	3"	380	3.58	2.04	1.88	0.67	PA0500GUAX16SA
PV0700GUAX24	3/4"	2"	250	2.58	2.04	2.00	0.79	
PV0700GUAX26	3/4"	3"	280	3.58	2.04	1.88	0.79	PA0700GUAX26SA
PV1000GUAX36	1"	3"	420	3.58	2.35	2.19	0.92	PA1000GUAX36SA
PV1200GUAX47	1-1/4"	3-5/8"	480	4.33	2.73	2.75	1.13	PA1200GUAX47SA
PV1500GUAX59	1-1/2"	5"	1170	5.83	3.85	3.75	1.32	PA1500GUAX59SA
PV2000GUAX69	2"	5"	1250	5.83	4.10	4.00	1.60	PA2000GUAX69SA