

Stainless Steel Wallplates

C-Series



Features and Benefits

- Smooth contours provide a modern, clean aesthetic
- Available in Type 430 Stainless Steel (magnetic) for general commercial use and good corrosion resistance in indoor applications
- Also available in Type 302/304 (non-magnetic) Stainless Steel for superior chemical and corrosion resistance and harsh indoor or outdoor environments, such as hospitals and industrial applications
- Satin finish
- 27 configurations available
- Midway sizes available in some configurations
- Includes matching mounting screws

Ordering Information

| Description | Stainless Steel | | | |
|--|---|---------------------|-----------|----------|
| | Type 430 | Type 302/304 | | |
| 1-Gang | Duplex Receptacle | SL8 | SS8-40 | |
| | Decora®/Decora Plus™/GFCI | SL26 | SS26-40 | |
| | Toggle Switch | SL1 | SS1-40 | |
| | Single 1.406" Diameter Opening ¹ | SL7 | SS7-40 | |
| | Single 1.6" Diameter Opening ² | SL721 | SS721-40 | |
| | Single 2.15" Diameter Opening ³ | SL723 | SS723-40 | |
| | Blank | SL13 | SS13-40 | |
| | Duplex Midway | SLJ8-C | SSJ8-C40 | |
| | Decora® Midway | SLJ82-C | SSJ82-C40 | |
| | Toggle Midway | SLJ1-C | SSJ1-C40 | |
| | Blank Midway | SLJ13-C | SSJ13-C40 | |
| | 2-Gang | 1 Duplex Receptacle | SL748 | SS748-40 |
| | | 2 Duplex Receptacle | SL82 | SS82-40 |
| 2 Decora®/Decora Plus™/GFCI | | SL262 | SS262-40 | |
| 2 Toggle Switch | | SL2 | SS2-40 | |
| 1 Toggle Switch, 1 Decora®/Decora Plus™/GFCI | | SL126 | SS126-40 | |
| 1 Toggle Switch, 1 Duplex Receptacle | | SL18 | SS18-40 | |
| Single 2.15" Diameter Opening | | SL703 | SS703-40 | |
| Single 2.465" Diameter Opening | | SL701 | SS701-40 | |
| Blank | | SL23 | SS23-40 | |
| Duplex Midway | | SLJ32-C | SSJ32-C40 | |
| Decora® Midway | | SLJ62-C | SSJ62-C40 | |
| Toggle Midway | | SLJ2-C | SSJ2-C40 | |
| 3-Gang | Blank Midway | SLJ23-C | SSJ23-C40 | |
| | 3 Decora®/Decora Plus™/GFCI | SL263 | SS263-40 | |
| | 3 Toggle Switch | SL3 | SS3-40 | |
| Blank | SL33 | SS33-40 | | |

¹ Typical for 15 Amp and 20 Amp straight blade receptacles

² Typical for 20 Amp and 30 Amp locking receptacles

³ Typical for 30 Amp and 50 Amp power receptacles

Specifications

| Material Specifications | |
|----------------------------|--|
| Plate | 0.032" Stainless Steel, Type 302/304 or 430 as specified |
| Mechanical Specifications | |
| Size | Standard Size and Midway Size |
| Mount | Device Mount or Box Mount as specified |
| Gang | 1-, 2-, or 3-gang as specified |
| Standards & Certifications | |
| Applicable Standards | UL 514D |
| Certification/Listing | cULus |
| Warranty | |
| Product Warranty | 10 Years |

Visit our Website at:
www.leviton.com/wallplates
email: commercial@leviton.com

Q-1107A

051518

Leviton Manufacturing Co., Inc.
201 N Service Rd, Melville, NY 11747
Telephone: 1-800-323-8920 • FAX: 1-800-832-9538
Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): 1-800-824-3005

© 2018 Leviton Manufacturing Co., Inc. All rights reserved.

