

IEC Pin and Sleeve

Fused Circuit-Lock® Devices and Accessories

30 and 60 Ampere – North American Ratings

IP66
SUITABILITY



Rating					Fused Circuit-Lock® Devices	
Amps	Poles and Wires	Configuration Recep./ Conn.	Plug/ Inlet	AC Voltage	Mechanical Interlock	Mating Plug
30	3P 4W			120/240V	HBL430MIF12W	HBL430P12W
	3P 4W			3Ø 240V	HBL430MIF9W	HBL430P9W
	3P 4W			3Ø 480V	HBL430MIF7W	HBL430P7W
	3P 4W			3Ø 600V	HBL430MIF5W	HBL430P5W
	4P 5W			3ØY 277/480V	HBL530MIF7W	HBL530P7W
	4P 5W			3ØY 347/600V	HBL530MIF5W	HBL530P5W
60	3P 4W			120/240V	HBL460MIF12W	HBL460P12W
	3P 4W			3Ø 240V	HBL460MIF9W	HBL460P9W
	3P 4W			3Ø 480V	HBL460MIF7W	HBL460P7W
	3P 4W			3Ø 600V	HBL460MIF5W	HBL460P5W
	4P 5W			3ØY 120/208V	HBL560MIF9W	HBL560P9W

Note: 30A – 1 inch N.P.T. hub supplied; 60A – 1¼ inch hub supplied.

ACFSNO

MICPK30

CA3430MI

HBLRFT2

Auxiliary Contacts

Description

Auxiliary contact, normally open, A600 pilot duty, break before break.

Catalog Number

ACFSNO

Auxiliary contact, normally closed, A600 pilot duty, break before break.

ACFSNC

Watertight Closure Plug Kits

Description

For 30A Circuit-Lock® unfused and fused Pin & Sleeve mechanical interlocks.

Catalog Number

MICPK30

For 60 & 100A Circuit-Lock® unfused and fused Pin & Sleeve mechanical interlocks.

MICPK60

Replacement Flip Covers

Description

For 30A, 3 and 4 wire mechanical interlocks.

Catalog Number

CA3430MI

For 30A, 5 wire mechanical interlocks.

CA530MI

For 60A mechanical interlocks.

CA60MI

Replacement Mounting Feet

Description

Replacement mounting feet and screws for 30 & 60A fused mechanical interlocks.

Catalog Number

HBLRFT2*

Note: * Package of 10 feet and 10 screws.

Dimensions

