



GE  
Lighting

**72275 - GE-232-MV-N**

**GE LFL Multi-Volt ProLine™ Electronic Multivolt Instant Start Ballast**

- High performance electronic ballast for all general fluorescent applications
- Instant start electronic ballast for long lamp starting cycles and low initial cost
- Multi-Voltage Technology handles voltage from 120 to 277V
- Light-weight, Low Profile Housing
- Parallel lamp operation means system maintenance is easier to manage
- Anti-striation Control for better light quality, with no striations



**CAUTIONS & WARNINGS**

**Warning**

- Risk of Electric Shock
  - Properly ground ballast and fixture.
  - Turn power off before servicing--see instructions.

**GENERAL CHARACTERISTICS**

Lamp Type	Fluorescent -
Bulb	Electronic
Ballast Type	Multivolt Instant Start
Starting Method	Instant start
Lamp Wiring	Parallel
Line Voltage Regulation (+/-)	10.0 %
Case Temperature (MAX)	70.0 °C
Ballast Factor	Normal
Power Factor Correction	Active
Sound Rating	A (20-24 decibels)
Additional Info	Auto-restart/Thermally protected/Anti-striation control

**ELECTRICAL CHARACTERISTICS**

Supply Current Frequency	50.0 Hz
--------------------------	---------

**DIMENSIONS**

Weight	1.4 lb
Exit Type	
Remote Mounting Distance	18.0 ft
Remote Mounting Wire Gauge	18.0 AWG

**PRODUCT INFORMATION**

Product Code	72275
Description	GE-232-MV-N
Standard Package	Case
Standard Package GTIN	10043168722756
Standard Package Quantity	10
Sales Unit	Standard Pack
No Of Items Per Sales Unit	1
No Of Items Per Standard	10
Package	
UPC	043168722759