



Shielded Ethernet Cable Spool

Description

Rockwell Automation's Cat5e shielded and unshielded cable is designed to supply a reliable network connection in harsh surroundings. The high speed data rate allows more data to be transferred within a shorter period of time. By optimizing balance of twisted pair conductors inside a robust thermoplastic elastomer (TPE) jacket, data is protected from noise, chemicals, and mechanical issues to M₃l₃C₃E₃ environmental protection levels. Two and four pair polyurethane (PUR) robotic flex cable and enclosures are available for flex applications. High voltage, 600V Ethernet cable is available for use in cable tray with high voltage power cables. All ethernet media components are designed to perform above TIA 568-B.2 and ODVA ethernet standards. Rockwell Automation's Bulletin 1585 ethernet cables are optimized UTP and STP cables in many applications.



Specifications

Certifications	UL Listed and CEC
Conductor Material	Tinned copper stranded
Bend Radius	10 million cycles at 20 x diameter (TPE cable)
Data Rate	Up to 1 Gb/s, Cat 5e
Voltage	300V

Features

- Four- and eight-conductor styles
- Twisted pair shielded cable types, Cat 5e
- Twisted pairs maintain signal balance through cable to provide high noise immunity and return loss
- Designed to ODVA EtherNet/IP™ specifications and ISO IEC 24702
- Suitable for high noise environments M₃l₃C₃E₃
- Riser PVC cables used for general purpose environments
- PUR robotic cable used for flex applications, also Halogen-free
- 600V PVC cable designed to support high voltage applications
- 600V On-Machine rated cable for use in a cable tray shared with high voltage power cables

Cable and Color Code

Two-Pair	Four-Pair																								
 <table border="1" data-bbox="727 1104 873 1205"> <tr><td>White/Orange</td><td>□</td></tr> <tr><td>White/Green</td><td>□</td></tr> <tr><td>Orange</td><td>■</td></tr> <tr><td>Green</td><td>■</td></tr> </table>	White/Orange	□	White/Green	□	Orange	■	Green	■	 <table border="1" data-bbox="1170 1058 1317 1255"> <tr><td>White/Orange</td><td>□</td></tr> <tr><td>Orange</td><td>■</td></tr> <tr><td>White/Green</td><td>□</td></tr> <tr><td>Blue</td><td>■</td></tr> <tr><td>White/Blue</td><td>□</td></tr> <tr><td>Green</td><td>■</td></tr> <tr><td>White/Brown</td><td>□</td></tr> <tr><td>Brown</td><td>■</td></tr> </table>	White/Orange	□	Orange	■	White/Green	□	Blue	■	White/Blue	□	Green	■	White/Brown	□	Brown	■
White/Orange	□																								
White/Green	□																								
Orange	■																								
Green	■																								
White/Orange	□																								
Orange	■																								
White/Green	□																								
Blue	■																								
White/Blue	□																								
Green	■																								
White/Brown	□																								
Brown	■																								

Product Selection

Jacket Material	Cable Type	No. of Conductors	Jacket Color	Wire Size, AWG	Nominal Outer Diameter	Operating Temperature [C (F)]	Cable Rating	Cat. No.‡
Riser PVC	Foil and braided shield	8 (four pair)	Teal	26	5.84 mm (0.23 in.)	-40...+75 (-40...+167)	UL CMR; cUL CMG; TIA-568-B	1585-C8CB-S100
Robotic PUR		4 (two pair)			—		C(ETL)US TYPE CMX; TIA 568-B, Flex rated, Halogen-Free	1585-C4UB-S100
600V PVC		8 (four pair)	Teal	22	8.13 ± 0.38 mm (0.32 in.)	-20...+80 ° (-4...+176 °)	(UL) CMX, CMR; c(UL) CMG; (UL) PLTC or AWM 2570 80 °C 600V; TIA-568-B	1585-C8HB-S100
		8 (four pair)	Red				1585-C8EB-S100	
	4 (2 pair)	Teal	1585-C4HB-S100					
			Red				1585-C4EB-S100	

‡ Replace 100 (100 m) with 300 (300 m) or 600 (600 m) for additional standard cable lengths (example 1585-C4TB-S100 becomes 1585-C4TB-S600).

