



Split-Bolt
T&B Catalog Number:

10CA
 78378620057
 Active

UPC Number:
Status:
Description:

Type CA Aluminum Split-Bolt Connector with Spacer and Washer for Use on Copper, Aluminum Conductors. Conductor Range for Equal Main and Tap 2/0 Str.-2 Sol.

Features

Bolt, nut, pressure bar and contoured spacer of aluminum alloy. Pressure bar and contoured spacer made of electrolytic copper. Spacer is completely tin plated.
 Bolt and nut are anodized to prevent seizing of threads and reduce galvanic corrosion when in contact with copper conductor.

General

Style	Type CA
Wire Type	Copper, Aluminum
Material	Aluminum
Conductor Range for Equal Main and Tap	2/0 Str.-2 Sol.
Conductor Range Min. Tap with one Max.	2/0 Str.-6 Sol.
Main	

Dimension Information

A (inches)	7/8
B (inches)	0.443
C (inches)	1 1/8
D (inches)	2 1/16

Packaging

T&B Inner Pack	25
Package in Units	250
T&B Sold in UOM	Each
T&B Weight Per UOM	22 lbs. per 100

Notes

Blackburn Contax recommended when used on aluminum conductor.

Certifications

RoHS Compliance	Yes
-----------------	-----

Certifications



File Nbr:
 E9809

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
 www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321

