



## Rigid/IMC Conduit Fittings

**T&B Catalog Number:**

374AL

**UPC Number:**

78621082919

**Status:**

Active

**Description:**

1 1/2 in. Hub Connector, Aluminum. For use with Rigid/IMC Conduit.

### Features

Copper-free aluminum construction

Tapered internal threads for water-tight/dust-tight union

Threads relieved to prevent bottoming of conduit, ensuring sound assembly

Recessed sealing ring at box end; sealing ring captivated

Hardened steel/malleable iron/copper-free aluminum locknuts designed to provide high quality ground continuity; extended reach of locknut permits clamping on thin boxes and enclosures

### Application

To connect threaded metal conduit (ferrous rigid/non-ferrous rigid/PVC coated/or intermediate metal) to a threadless opening in a box or enclosure in outdoor or indoor location exposed to continuous or intermittent moisture.

To positively bond conduit to box or enclosure.

Suitable for hazardous locations use in Class I, Division 2; Class II, Division 1&2; Class III, Division 1 & 2 per NEC 501-4(b); 502-4 (a) and 503-3 (a).

Suitable for hazardous locations use in Class II, Groups E, F, G & Class III locations per CEC 18-202; 18-252; 18-302; 18-352.

When used with neoprene O-ring, provides water-tight threaded hub on enclosures

UL Listed 105 degree C

### General

Trade Size (inches)

1-1/2

Material

Aluminum

### Dimension Information

Dimension A (inches)

3 3/32

Dimension B (inches)

1 5/8

Dimension C (inches)

1

### Specifications

3dmodel

Available on Website

### Packaging

T&B Inner Pack

2

Package in Units

10

T&B Sold in UOM

Each

T&B Weight Per UOM

40 lbs. per 100

### Application Support

Spacing Chart

Available on Website

## Notes

Available with DURA-PLATE Finish

## Certifications

RoHS Compliance

Yes

## Certifications



File Nbr:

E 23018

### For further technical assistance, please contact us...

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
www.tnb.com

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com