



E-Z-Ground Compression Grounding T&B Catalog Number:

UPC Number: 54875L
78621017986
Status: Active
Description:

E-Z-Ground Figure 6-6 Copper Compression Ground Grid Connector for Cable Range #2 Str. - 250 kcmil, Ground Rod 5/8 - 1/2

Features

E-Z-Ground® connectors are designed for direct burial and offer a safe, efficient alternative to exothermic welding products.

General

Style	Figure 6-6
Material	Copper
Wire Range	#2 Str. - 250 kcmil
Cable to Cable Element A	#2 Str.-250 kcmil
Cable to Cable Element B	#2 Str.-250 kcmil
Element B to Ground Rod	5/8 - 1/2
Element B to Rebar	3/8 - 1/2 #3-#4 Rebar

Dimension Information

D (inches)	7/8
T (inches)	3/4

Tooling

Die Selection Charts	Available on Website
Application Tools	TBM14M, 13100A, TBM15I

Packaging

Package in Units	25
T&B Sold in UOM	Each
T&B Weight Per UOM	0.77 lbs. per 100

Application Support

MSDS Number	msds-0085-tb2
Overview	Available on Website

Notes

Meets IEEE 837 Requirements.

Certifications



File Nbr:
Y

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com