



# Color-Keyed®

## E-Z-Ground Compression Grounding

T&B Catalog Number:

54900L

UPC Number:

78621017964

Status:

Active

Description:

E-Z-Ground Figure 6-6 Copper Compression Ground Grid Connector for Cable Range 250 kcmil - 500 kcmil, Ground Rod 5/8 - 3/4

### Features

E-Z-Ground® connectors are designed for direct burial and offer a safe, efficient alternative to exothermic welding products.



### General

Style	Figure 6-6
Material	Copper
Wire Range	250 kcmil - 500 kcmil
Cable to Cable Element A	250 kcmil-500 kcmil
Cable to Cable Element B	#2 Str.-250 kcmil
Element B to Ground Rod	5/8 - 3/4
Element B to Rebar	5/8 - 3/4 #5 - #6 Rebar

### Dimension Information

D (inches)	7/8
T (inches)	1 3/8

### Tooling

Die Selection Charts	Available on Website
Application Tools	TBM14M, 13100A, TBM15I

### Packaging

T&B Order Multiple	1
Package in Units	25
T&B Sold in UOM	Each
T&B Weight Per UOM	2.35 lbs. Each

### Application Support

MSDS Number	sds-00045-tb2
T&B Instruction Sheets	ta02146-tb2
Overview	Available on Website

### Notes

Meets IEEE 837 Requirements.

### Certifications



File Nbr:  
E9809

For further technical assistance, please contact us...

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289

