



H-Tap
T&B Catalog Number:

63148

UPC Number:

78621063148

Status:

Active

Description:

Aluminum H-Tap for Wire Range Main: 4/0-2/0, Branch 3/0-1, Blue D

Features

Fillerlok Tab provides positive interlock and extends wire range.

Wire Bore coated with T&B oxide inhibitor.

Recommended for aluminum to aluminum, aluminum to copper, and copper to copper connectors.

General

Material	Aluminum
Wire Size	4/0-2/0
Die Color	Blue
Die Code	D
Side Tap	8-14

Dimension Information

L (inches)	3
------------	---

Specifications

Voltage Rating	600V
----------------	------

Accessories & Components

Soft Shell Cover	HTC40C
Hard Cover	HTC500

Tooling

Application Tools	TBM15I
Die Catalog Number	15502
Connector & Tooling Chart	Available on Website

Packaging

T&B Order Multiple	1
T&B Inner Pack	1
Package in Units	25
T&B Sold in UOM	Each
T&B Weight Per UOM	24 lbs. per 100

Notes

For 1 CU or AL, Branch wire bent double (hair pin).

Requires adapter catalog number 15500-TB when used with hydraulic head TBM15I.

Certifications

RoHS Compliance	Yes
-----------------	-----

Certifications



File Nbr:
 140B

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com