



**Dual-Rated
T&B Catalog Number:**

ADR50-34
78378661030

UPC Number:

Active

Status:

Description:

Type ADR-ALCUL Three-Conductor, Four-Hole Mount for Conductor Range Max 500 kcmil, Min 4 Str.

Features

Easy Installation - no special tools required.

General

Style	ALCUL Three-Conductor, Four-Hole Mount
Material	Aluminum
Plating	Tin-Plated
Conductor Range (AL or CU) Maximum	500 kcmil
Conductor Range (AL or CU) Minimum	4 Str.

Dimension Information

Length (inches)	4 11/16
Width (inches)	3 3/4
Height (inches)	1 9/16
D (inches)	5/8
E (inches)	1/2
F (inches)	7/16
G (inches)	3 5/16
I (inches)	1 1/4

Packaging

T&B Order Multiple	3
T&B Inner Pack	3
Package in Units	30
T&B Sold in UOM	Each
T&B Weight Per UOM	101.25 lbs. per 100

Notes

NEMA spacing 1 3/4 inch centers.

Connectors accomodating conductors 600 kcmil and larger have double rows of set screws (D suffix).

UL 486B tested, AL9CU rated

Certifications

RoHS Compliance	No
-----------------	----

Certifications



File Nbr:
E9809

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321

