



**Cable Tie**  
**T&B Catalog Number:**

CSS-270  
 78621070067  
 Active

**UPC Number:**  
**Status:**  
**Description:**

Cable Tie Deltec 1/2 in. x 27 in. Double-locking head

**Features**

Perfect for coaxial, fiber optic and all other communication and electrical conducting cables.  
 Strap and body are weatherable acetal, offering superior resistance to sunlight, moisture and salt environments.  
 Locking device is marine-grade corrosion-resistant copper alloy.

**Application**

Ideal solution for bundling in harsh outdoor environments.

**General**

Material	Weather-Resistant Acetel
Color	Black

**Dimension Information**

Length (inches)	27
Width (inches)	.500
Max. Wire Bundle Diameter (inches)	8

**Specifications**

Temperature Rating	-30°F to 150°F
--------------------	----------------

**Tooling**

Application Tools	WT3D
-------------------	------

**Packaging**

T&B Order Multiple	25
Package in Units	500
T&B Sold in UOM	Each
T&B Weight Per UOM	4.83 lbs. per 100

**Notes**

The recommended maximum continuous static loading for the Deltec® straps is 20 lbs. Per strap. For best results suggested spacing is 15 inches. It is the responsibility of the user to determine whether or not their application meets our recommendation.

**Certifications**

RoHS Compliance	Yes
-----------------	-----

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
 www.tnb.com

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321

