



**Strap on a Reel**  
**T&B Catalog Number:**

CSS-50R  
 78621070069  
 Active

**UPC Number:**  
**Status:**  
**Description:**

Cable Tie Deltec 1/2 in. x 50 ft. Reel of Strap

**Features**

Perfect for coaxial, fiber optic and all other communication and electrical conducting cables.

Strap and body are weatherable acetal, offering superior resistance to sunlight, moisture and salt environments.

Locking device is marine-grade corrosion-resistant copper alloy.

**Application**

Ideal solution for bundling in harsh outdoor environments.

**General**

Material Weather-Resistant Acetel  
 Color Black

**Dimension Information**

Length (feet) 50  
 Width (inches) .500

**Specifications**

Temperature Rating -30°F to 150°F

**Tooling**

Application Tools WT3D

**Packaging**

T&B Order Multiple 10  
 Package in Units 10  
 T&B Sold in UOM Each  
 T&B Weight Per UOM 101.88 lbs. per 100

**Notes**

The recommended maximum continuous static loading for the Deltec® straps is 20 lbs. Per strap. For best results suggested spacing is 15 inches. It is the responsibility of the user to determine whether or not their application meets our recommendation.

**Certifications**

RoHS Compliance Yes

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
 www.tnb.com

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email:techsupport@tnb.com