



Carlon®

ENT Flexible Raceway
T&B Catalog Number:

12011-500
 03448100283
 Active

UPC Number:
Status:
Description:

2 in. Flex-Plus ENT non-metallic blue flexible raceway, 500 ft.

Features

- Recognized for use with PVC rigid non-metallic conduit fittings with all size of ENT.
- One piece ENT coupling, threaded terminator and rigid non-metallic conduit fittings are rated concrete tight without tape.
- Lightweight, hand bendable, and free from sharp edges which reduces installation time and saves money.

Application

- Flex-Plus Blue ENT is a non-metallic flexible raceway for use in walls, floors, and non-plenum ceilings.
- Residential, low or high rise, multi or single family. Commercial applications - low or high rise - office, retail, hotel/motel and restaurants.
- Other applications include schools, classrooms, dormitories, offices, fire alarm systems, solar photovoltaic systems, recreational vehicles and parks, and marinas and boatyards.

General

Pull Tape	Empty
Material	PVC
Color	Blue
Reel Length (feet)	500
Reel Type	Wood
Reel Size (Feet x Width)	48 x 32
Component Type	Flexible Raceway

Dimension Information

Size (inches)	2
Nominal Inside Diameter (inches)	2.03
Nominal Outside Diameter (inches)	2.375
Minimum Bend Radius (inches)	9 1/2

Packaging

T&B Order Multiple	500
Package in Units	500
T&B Sold in UOM	Feet
T&B Weight Per UOM	0.47 lbs. Each

Application Support

Product Specifications-Flex-Plus Blue ENT	Available on Website
Application Handbook-ENT	Available on Website

Product Overview-Flex-Plus Blue ENT Available on Website

Product Overview-Flex-Plus Blue ENT Accessories Available on Website

cessories

Notes

1-1/4 in. - 2 in. available in yellow and red.

Certifications

RoHS Compliance

Yes

Certifications



File Nbr:

E 73317

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com