



Carlon®

Liquidtight Flexible Non-Metallic Conduit & Fittings

T&B Catalog Number:

15008-100

UPC Number:

03448123328

Status:

Active

Description:

1 inch gray liquidtight flexible non-metallic conduit, 100 ft. coil.

Features

- Non-conductive and non-corrosive.
- Lightweight for easy handling, transportation and installation.
- Crush, abrasion and strain resistant.
- Provides superior wire protection
- Smooth interior ideal for pulling cable, no jagged edges.
- Maintains internal I.D. even in tight radius bends.
- Resistant to oil, acid, ozone, and alkaline.
- UL listed for outdoor use and sunlight resistant.
- UL listed for use as indicated in Article 356.2 of the NEC and Section 12-1300 of the Canadian Electrical Code, Part 1.
- Suitable for use at conduit temperatures of 80 degree C dry, 60 degree C wet and 60 degree C oil resistant as required by Section 15-6 of ANSI/NFPA 79 and UL 1660.
- Sequentially market footage

Application

- Control and Motor
- Air conditioning and heating
- Computer power distribution
- Machine Tools
- Console wiring
- Transformer connections
- Outdoor lighting

General

Material	Non-Metallic
Color	Gray

Dimension Information

Size (inches)	1
Average O.D. (inches)	1.302
Average I.D. (inches)	1.046
Nominal Size (inches)	1
Coil Length (feet)	100

Packaging

T&B Order Multiple	100
Package in Units	100
T&B Sold in UOM	Feet
T&B Weight Per UOM	0.28 lbs. Each

Application Support

Available on Website

Product Overview-Carflex Liquidtight Flexible Tubing

Notes

Available in black and gray.

Customer cut lengths available.

Certifications

RoHS Compliance

Yes

Certifications



File Nbr:

E 79553

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com