



# T&B®

**Liquidtight Flexible Metal Conduit Fittings**  
**T&B Catalog Number:**

**UPC Number:** 5241  
 78621005241  
**Status:** Active  
**Description:**

3/8 in. 45 degree malleable iron liquidtight connector

**Features**

Ability to install quickly with low torque effort

**Application**

Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.

To positively bond conduit to box or enclosure.

**General**

Trade Size (inches)	3/8
Material	Malleable Iron
Finish	Electro Zinc Plated/Chromate Coating

**Dimension Information**

Dimension A (inches)	1 5/32
Dimension B (inches)	1 9/16
Dimension C (inches)	9/16

**Specifications**

3dmodel Available on Website

**Accessories & Components**

Wiremesh Grips for Liquidtight Fittings WMG-LT1

**Packaging**

T&B Inner Pack	25
Package in Units	50
T&B Sold in UOM	Each
T&B Weight Per UOM	17.9 lbs. per 100

**Certifications**

RoHS Compliance Yes

**Certifications**



File Nbr:  
 E 23018

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
 www.tnb.com

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321

