

4821L -- Industrial Grade Toggle Switch




Single Pole, Double Throw, 15A 120/277V AC, Momentary Contact, Center Off, Locking

Product Specifications

Type	Special Purpose AC
Grade	Industrial
Actuator	Toggle
Special Purpose Switch Positions	3 Position 2 Circuit Center Off Momentary.
Actuator Type	Standard
Switch Contact Type	Single Pole, Double Throw
Amperage	15A
Amperage/Voltage Rating	120/277V AC
Packaging	Single
Wiring Style	Back & Side Wired
Termination Type	Combo Philips/Slotted/Robertson
Base Material	Thermoset.
Face Material	Thermoset, Color coded by voltage.
Toggle/Actuator Material	Valox..
Terminals	High Performance Copper Alloy.
Mounting Yoke	Brass and Nickel Plated Steel.
Contacts	Silver Cadmium Oxide.
Movable Contact Arm	High Performance Copper Alloy.
Rocker	Thermoplastic Elastomer.
Ground Terminal	Brass and Nickel Plated Steel.
Terminal Screws	Brass.
Ground Screw	Brass (green).
Auto Ground Clip	Stainless Steel.
Dielectric Voltage	Withstands 1500V Minimum.
Max. Working Voltage	277V AC

Overload	Minimum 4.8 times rated current for 100 cycles.
Temp. Rise	30 deg. C maximum at rated current.
Max. Continuous Current	15A
Terminal Accomodation	#14 AWG min.- #10 AWG max.
Flammibility	UL 94 V2.
Operating Temperature	Maximum continuous 75 deg. C- Minimum -40 dec. C (w/o impact).
UL Certification	UL Listed, File E1464, Guide #WMUZ.
Standards	Complies with UL 20 and NEMA WD-1.
Catalog Page	Click here for catalog page
UPC Number	78178665725
Weight in LBs	0.2



BRYANT®