



Blackburn®

Dual-Rated
T&B Catalog Number:

ASR2506
 78378613323
 Active

UPC Number:
Status:
Description:

Type ASR-ALCUL Splice Reducer with Solid Barrier Wire Stop for Conductor Range Max 250 kcmil, Min 6 Str.

Features

Easy Installation - no special tools required.

General

Style	ALCUL Splice Reducer with Solid Barrier Wire Stop
Material	Aluminum
Plating	Tin-Plated
Conductor Range (AL or CU) Maximum	250 kcmil
Conductor Range (AL or CU) Minimum	6 Str.

Dimension Information

Length (inches)	2 1/8
Width (inches)	55/64
Height (inches)	31/32
I (inches)	1 7/64

Packaging

Package in Units	12
T&B Sold in UOM	Each
T&B Weight Per UOM	33.33 lbs. per 100

Notes

UL 486B tested, AL9CU rated

Certifications



File Nbr:
 E9809

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
 www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com

