

Products

- › [Index](#)
- › [Featured Products](#)
- › [Cross Reference](#)
- › [UPC Search](#)

**Product Datasheet**

[Catalog Home](#)

[Home Page](#)

[Search](#)

## 1482 -- Combination Coupling 1/2" EMT to 1/2" Flex



**Product Specifications**

<b>Family</b>	Flexible Metal Conduit Fittings & EMT Fittings
<b>Fittings Classification</b>	Combination Couplings
<b>Sub Class</b>	EMT Flex Screw In Compression

<b>Trade Size</b>	1/2"
<b>Standard Packaging</b>	Carton
<b>Flex Size</b>	1/2"
<b>EMT Size</b>	1/2"
<b>WT. PER HU.</b>	8
<b>Dimension A</b>	.84"
<b>Dimension B</b>	1.10"
<b>Unit Carton Quantity</b>	50
<b>Ship Carton Quantity</b>	500
<b>UPC Number</b>	050169014820
<b>Product UPC-A Labeled</b>	No
<b>Catalog PDF Page</b>	<a href="#">PDF Catalog Page</a>

#### Applications

- For use when coupling flexible metal conduit to EMT conduit
- Use RACO® Cat. Nos. 1482-1484 when coupling flexible metal conduit to EMT

#### Product Features

- Rugged metallic construction insures mechanical protection

#### Compliances

UL 514-B listed, File E195969 C/UL C / UL / US

#### Nail-Up Straps Application

- For use in mounting EMT flexible metal conduit, armored cable, and MC cable

#### Nail-Up Straps Product

- Stamped steel straps are pregalvanized for added corrosion protection