

Products

- > [Index](#)
- > [Featured Products](#)
- > [Cross Reference](#)
- > [UPC Search](#)

**Product Datasheet**

[Catalog Home](#) [Home Page](#)

[Search](#)

## 1942 -- Combination Coupling 1/2" Flex to 1/2" EMT



**Product Specifications**

<b>Family</b>	Flexible Metal Conduit Fittings & EMT Fittings
<b>Fittings Classification</b>	Combination Couplings
<b>Sub Class</b>	Flex Coupling Squeeze Compression
<b>Trade Size</b>	1/2"
<b>Standard Packaging</b>	Carton
<b>Flex Size</b>	1/2"
<b>EMT Size</b>	1/2"
<b>Ship Carton Length</b>	6.25
<b>Ship Carton Width</b>	4.5
<b>Ship Carton Height</b>	4.25
<b>WT. PER HU.</b>	16.2
<b>Dimension A</b>	1-1/2"
<b>Dimension B</b>	1-3/4"
<b>Dimension C</b>	1-7/64"
<b>Dimension D</b>	23/32"
<b>Dimension E</b>	13/16-15/16"
<b>Unit Carton Quantity</b>	25
<b>Ship Carton Quantity</b>	25
<b>UPC Number</b>	050169019429
<b>Product UPC-A Labeled</b>	Yes

**Applications**

- Use RACO® Cat. Nos. 1941-1943 when coupling flexible metal conduit to EMT

**Product Features**

- Rugged metallic construction insures mechanical protection
- All steel/malleable components are zinc electro plated for corrosion protection

**Compliances**

UL 514-B listed, File E195969 C/UL

