

Products

- › [Index](#)
- › [Featured Products](#)
- › [Cross Reference](#)
- › [UPC Search](#)

Product Datasheet

[Catalog Home](#)[Home Page](#)[Search](#)**2720AJ -- REDI-LOC® II Connector**

Product Specifications

Family	Metal Clad Cable Connectors
Fittings Classification	Steel - Snap In Connectors
Trade Size	1/2"
Cable Range	AC: AL & Steel 14/3-10/3; MC:MCI: Steel & AL:12/2-10/3; MCI-A: Steel and AL:12/3-10/3; HCF: AL 12/3-10/3; 3/8" RWF MC: Steel and AL; Cable Range Diam. .460" min. to .600" max.
Standard Packaging	Carton
Ship Carton Length	12.125
Ship Carton Width	9.4375
Ship Carton Height	10.5
WT. PER HU.	3.7
Dimension A	1.070
Dimension B	.840
Dimension C	.840
Unit Carton Quantity	50
Ship Carton Quantity	500
UPC Number	050169927205
Inner Leaf 2 of 5 Bar Code	50050169927200
COUNTRY OF ORIGIN	MADE IN THE U.S.A.

Applications

- For use in dry locations to connect MCI, MCI-A, AC and HCF cable to a box or enclosure

Product Features

- Patented snap-in design -- MCI, AC and HCF Cable can be securely installed in outlet boxes or enclosures in seconds, without tools or locknuts
- Redi-Loc® Connectors cut installation time be 33% over competing termination methods
- Compact single unit design -- no need to worry about loose components or fumbling with protruding hardware
- Snaps tightly into the knockout -- no need to worry about a loose connection
- Reusable design -- installation can be reversed just as easily as it was originally installed
- Integral red insuliner -- provides for maximum wire protection and liner visibility for inspecting authorities
- Durable all steel construction
- Zinc electroplated -- for corrosion protection
- Tri-lingual (English, Spanish and French) installation instructions included in each unit carton
- RACO MCI, AC and HCF connectors are suitable for applications up to 600 V

Compliances

cULus