

Products

- › [Index](#)
- › [Featured Products](#)
- › [Cross Reference](#)
- › [UPC Search](#)

Product Datasheet

[Catalog Home](#)[Home Page](#)[Search](#)

3314DB -- Double Bite Saddle Connector Straight 3-1/2" Trade Size Insulated



Product Specifications

Family	Double Bite Saddle Connector
Fittings Classification	Double Bite Saddle Connector
Sub Class	Insulated
Trade Size	3-1/2"
Standard Packaging	Carton
Ship Carton Length	5.5
Ship Carton Width	5.1
Ship Carton Height	4.7
WT. PER HU.	225.0
Dimension A	2-15/16"
Dimension B	4-3/4"
Dimension C	1"
Unit Carton Quantity	1
Ship Carton Quantity	1
UPC Number	050169533147
Inner Leaf 2 of 5 Bar Code	50050169533142

Applications

- Use RACO DOUBLE BITE saddle connectors in dry locations to connect flexible metal conduit, MCI, MCI-A and AC cable to a box or enclosure

Product Features

- Straight connectors have all steel construction that ensures mechanical protections for raceways
- The straight connectors are available in 3/8" to 4" trade sizes
- 90° connectors have malleable iron & steel construction for added strength

- 90° connectors are available in 3/8" to 1" trade sizes
- Dual saddle clamp ensures proper conduit and cable connection for raceway
- Zinc plated for corrosion resistant installation
- Tri-head screw/clamp design - connectors can be installed by using a slotted, Phillips or Robertson head screwdriver
- Insulated throats for all DOUBLE BITE provides for maximum wire protection
- RACO DOUBLE BITE saddle connectors comply with UL standard 514B and NEMA FB-1. No need to worry about code compliances

Compliances
C / UL / US

[Login](#) | [Privacy](#) | [Site Map](#)