

Products

- › [Index](#)
- › [Featured Products](#)
- › [Cross Reference](#)
- › [UPC Search](#)

Product Datasheet

[Catalog Home](#)[Home Page](#)[Search](#)

3422DC -- 90 Degree Liquidtight Connector 1/2" Trade Size - Die Cast Zinc



Product Specifications

Family	Liquidtight Conduit and Cord Connectors
Fittings Classification	Die Cast Zinc - 90 Degree Connectors
Sub Class	Uninsulated
Trade Size	1/2"
Standard Packaging	Carton
Ship Carton Length	17.3
Ship Carton Width	6.3
Ship Carton Height	6.5
WT. PER HU.	16.3
Unit Carton Quantity	25
Ship Carton Quantity	100
UPC Number	050169980125

Applications

- For use in outdoor or indoor locations on flexible metallic liquidtight conduit and Type B flexible nonmetallic liquidtight conduit
- Use to positively bond the conduit to a box or enclosure
- RACO®

Product Features

- Gland-ring is designed to slip onto the conduit quickly and to grip the jacket of the conduit, speeding installation, assuring a perfect seal, and preventing pullouts
- All components are reusable -- RACO® liquidtight connectors may be easily disassembled and reused after years of service
- Sealing washer (included) provides a liquidtight seal when

- terminating the connector in a threadless opening
- Locknut included with every RACO® liquidtight connector assures continuity of ground
 - Zinc Die Cast

Compliances

cULus

[Login](#) | [Privacy](#) | [Site Map](#)