

Products

- > [Index](#)
- > [Featured Products](#)
- > [Cross Reference](#)
- > [UPC Search](#)

Product Datasheet

[Catalog Home](#)[Home Page](#)[Search](#)

3526-3 -- 4" Trade Size Straight Liquidtight with #6 - #250 MCM Grounding Lug



Product Specifications

Family	Liquidtight Conduit and Cord Connectors
Fittings Classification	Grounding Liquidtight Connectors
Sub Class	Insulated
Trade Size	4"
Standard Packaging	Carton
Ship Carton Length	6.5
Ship Carton Width	6.5
Ship Carton Height	5.125
WT. PER HU.	617.7
Dimension A	5-35/64"
Dimension B	1-5/32"
Thread Spec. B	4-8 NPT
Dimension C	3-5/8"
Dimension D	1-13/16"
Unit Carton Quantity	1
Ship Carton Quantity	1
UPC Number	050169352632

Applications

- For use in outdoor or indoor locations on flexible metallic liquidtight conduit, when installation of a copper or aluminum external bonding jumper is required
- RACO® grounding liquidtight connectors are suitable for use in Class 1, Division 2; Class 2, Division 1 and 2; and Class 3, Division 1 and 2 hazardous locations

Product Features

- Patented split gland-ring is designed to slip onto the conduit quickly and to grip the jacket of the conduit, speeding installation, assuring a perfect seal, and preventing pullouts
- All components are reusable -- RACO® liquidtight connectors may be easily disassembled and reused after years of service
- Sealing washer (included) provides a liquidtight seal when terminating the connector in a threadless opening
- Heavy duty locknut included with every RACO® liquidtight connector assures continuity of ground
- All metallic components are zinc electro plated for added corrosion protection
- Bodies - 3/8" to 1" Steel ; 1-1/4" to 4" Malleable Iron ; •Nuts - 3/8" to 1" Steel ; 1-1/4" to 4" Malleable Iron

Compliances

UL CSA

