

Products

- > [Index](#)
- > [Featured Products](#)
- > [Cross Reference](#)
- > [UPC Search](#)

Product Datasheet

[Catalog Home](#)[Home Page](#)[Search](#)

3546DC -- 90 Degree Liquidtight Connector 1-1/2" Trade Size - Die Cast Zinc -Insulated



Product Specifications

Family	Liquidtight Conduit and Cord Connectors
Fittings Classification	Die Cast Zinc - 90 Degree Connectors
Sub Class	Insulated
Trade Size	1-1/2"
Standard Packaging	Carton
Ship Carton Length	8.1
Ship Carton Width	6.1
Ship Carton Height	6.1
WT. PER HU.	85.0
Ship Carton Quantity	5
UPC Number	050169980309

Applications

- For use in outdoor or indoor locations on flexible metallic liquidtight conduit and Type B flexible nonmetallic liquidtight conduit
- Use to positively bond the conduit to a box or enclosure
- RACO®

Product Features

- Gland-ring is designed to slip onto the conduit quickly and to

grip the jacket of the conduit, speeding installation, assuring a perfect seal, and preventing pullouts

- All components are reusable -- RACO® liquidtight connectors may be easily disassembled and reused after years of service
- Sealing washer (included) provides a liquidtight seal when terminating the connector in a threadless opening
- Locknut included with every RACO® liquidtight connector assures continuity of ground
- Zinc Die Cast

Compliances

cULus