

Products

- › [Index](#)
- › [Featured Products](#)
- › [Cross Reference](#)
- › [UPC Search](#)

Product Datasheet

[Catalog Home](#)[Home Page](#)[Search](#)

3703-2 -- Cord Grip Connector 3/4" Trade Size .375 - .500



Product Specifications

Family	Liquidtight Conduit and Cord Connectors
Fittings Classification	Steel / Malleable Iron Strain Relief Connectors
Sub Class	3/4 inch Hubs Form 3
Trade Size	3/4"
Cable Range	.375 - .500
Standard Packaging	Carton
Ship Carton Length	8.25
Ship Carton Width	5.00
Ship Carton Height	4.00
WT. PER HU.	20.4
Dimension A	1-29/64"
Thread Spec. A	3/4-14 NPT
Dimension B	19/32"
Dimension C	1-9/16"
Unit Carton Quantity	25
Ship Carton Quantity	25
UPC Number	050169370322

Applications

- For use in wet or dry locations to provide a liquidtight and strain relief termination for flexible cord and cable
- RACO® liquidtight strain relief cord connectors are suitable for use in Class 1, Division 2; Class 2, Division 1 and 2; and Class 3, Division 1 and 2 hazardous locations

Product Features

- All steel/malleable construction provides mechanical strength
- Unique Neoprene grommet design -- grommet is forced up and around the cord when the nut is tightened for a positive liquidtight seal
- Washers have size range imprinted for identification -- eliminates misidentifying inventory
- Use RACO® locknuts and sealing washers to complete a liquidtight installation on a sheet metal box or panel
- All metallic components are zinc electro plated for corrosion protection
- Bodies - 3/8" to 1-1/2" Malleable Iron; Nuts - 3/8" to 1" Steel, 1-1/4" Malleable Iron

Compliances

C/UL/US

