

Products

- > [Index](#)
- > [Featured Products](#)
- > [Cross Reference](#)
- > [UPC Search](#)

Product Datasheet

[Catalog Home](#)[Home Page](#)[Search](#)

3705-1 -- Cord Grip Connector 1-1/4" Trade Size .850 - 1.000



Product Specifications

Family	Liquidtight Conduit and Cord Connectors
Fittings Classification	Steel / Malleable Iron Strain Relief Connectors
Sub Class	1 1/4 Hubs Form 5
Trade Size	1-1/4"
Cable Range	.850 - 1.000
Standard Packaging	Carton
Ship Carton Length	8.25
Ship Carton Width	8.25
Ship Carton Height	6.00
WT. PER HU.	53.8
Dimension A	2-3/16"
Thread Spec. A	1-1/4-11-1/2 NPT
Dimension B	5/8"
Dimension C	2-1/32"
Unit Carton Quantity	25
Ship Carton Quantity	25
UPC Number	050169370513

Applications

- For use in wet or dry locations to provide a liquidtight and strain relief termination for flexible cord and cable
- RACO® liquidtight strain relief cord connectors are suitable for use in Class 1, Division 2; Class 2, Division 1 and 2; and Class 3, Division 1 and 2 hazardous locations

Product Features

- All steel/malleable construction provides mechanical strength
- Unique Neoprene grommet design -- grommet is forced up and around the cord when the nut is tightened for a positive liquidtight seal
- Washers have size range imprinted for identification -- eliminates misidentifying inventory
- Use RACO® locknuts and sealing washers to complete a liquidtight installation on a sheet metal box or panel
- All metallic components are zinc electro plated for corrosion protection
- Bodies - 3/8" to 1-1/2" Malleable Iron; Nuts - 3/8" to 1" Steel, 1-1/4" Malleable Iron

Compliances

C/UL/US

