

Products

- > [Index](#)
- > [Featured Products](#)
- > [Cross Reference](#)
- > [UPC Search](#)

Product Datasheet

[Catalog Home](#)[Home Page](#)[Search](#)

3706-2 -- Cord Grip Connector 1-1/2" Trade Size 1.250 - 1.400



Product Specifications

Family	Liquidtight Conduit and Cord Connectors
Fittings Classification	Steel / Malleable Iron Strain Relief Connectors
Sub Class	1 1/2 Hubs Form 6
Trade Size	1-1/2"
Cable Range	1.250 - 1.400
Standard Packaging	Carton
Ship Carton Length	8.25
Ship Carton Width	6.00
Ship Carton Height	5.5
WT. PER HU.	80.5
Dimension A	2-1/2"
Thread Spec. A	1-1/2-11-1/2 NPT
Dimension B	5/8"
Dimension C	2-7/32"
Unit Carton Quantity	10
Ship Carton Quantity	10
UPC Number	050169370629

Applications

- For use in wet or dry locations to provide a liquidtight and strain relief termination for flexible cord and cable
- RACO® liquidtight strain relief cord connectors are suitable for use in Class 1, Division 2; Class 2, Division 1 and 2; and Class 3, Division 1 and 2 hazardous locations

Product Features

- All steel/malleable construction provides mechanical strength
- Unique Neoprene grommet design -- grommet is forced up and around the cord when the nut is tightened for a positive liquidtight seal
- Washers have size range imprinted for identification -- eliminates misidentifying inventory
- Use RACO® locknuts and sealing washers to complete a liquidtight installation on a sheet metal box or panel
- All metallic components are zinc electro plated for corrosion protection
- Bodies - 3/8" to 1-1/2" Malleable Iron; Nuts - 3/8" to 1" Steel, 1-1/4" Malleable Iron

Compliances

C/UL/US

