















ACCESSORIES

Mounting Accessories

SURFACE MOUNT HANGERS




| Surface Mount Hangers | Cat. No. | Description | For Use With |
|---|----------|--|--|
|  | ITB-4 | Hanger for mounting close to ceiling on T-Bar grid system | All surface mounted fixtures |
|  | CS-2 | Ceiling spacer for mounting directly to outlet box. Used for mounting fixtures below combustible low density cellulose fiberboard ceilings. Maintains 1½" spacing. | All surface mounted fixtures |
|  | CS-4 | All purpose spacer (1½" × 2¼" × 4"), maintains 1" spacing on any type of installation | All surface mounted fixtures |
|  | CS-5 | All purpose spacer with special T-Bar clip and stud for mounting to an inverted T-Bar ceiling. Maintains 1½" spacing. | All surface mounted fixtures |
|  | CSZT | Zip tee hanger 1½" spacer. Designed for 15/16" wide T-Bars. | CS, LCS, and CSR series except fluorescent HO and VHO models |
| | KZT | Zip tee hanger 1½" spacer. Designed for 15/16" wide T-Bars. | K and KL |
|  | CSTH | Slide tong hanger for ungrooved channel. Maintains 1½" spacing. | CS, LCS, and CSR (Use KTH for fluorescent HO and VHO) |
|  | KTH | Slide tong hanger with 7/8" hole. Maintains 1½" spacing. | K and KL |
|  | LHVTH | Slide tong hanger with 7/8" hole. | LHV and LHA |
|  | LHSH6 | Slide tong hanger with 5/16" holes | LHR 6-Lamp fixtures |
| | LHSH4 | Slide tong hanger with 5/16" holes | LHR 4-Lamp fixtures |
|  | PEBU | End surface mounting bracket for 2H3S hub options | LU, FNPS |
| | PEBUHSMS | End surface mounting bracket for 2H and 2HS hub options | FNPV, FNPS |
|  | PEBA | End surface mounting bracket with 90° adjustment for 2H3S hub options | LU, FNPS |
| | PEBASMS | End surface mounting bracket with 90° adjustment for 2H and 2HS hub options | FNPV, FNPS |
|  | PTBS | Surface mounting bracket, 304 Stainless steel, 2 brackets | FNPV, FNPS, FDPS, FNPH, FDPH |
| | PTBS3 | Surface mounting bracket, 304 Stainless steel, 3 brackets | FNPV, FNPS, FDPS, FNPH, FDPH |
|  | PTBA | Surface mounting bracket, 304 Stainless steel, wall mount with 90° adjustment in 15° increments, 2 brackets | FNPV, FNPS, FDPS, FNPH, FDPH |
| | PTBA3 | Surface mounting bracket, 304 Stainless steel, wall mount with 90° adjustment in 15° increments, 3 brackets | FNPV, FNPS, FDPS, FNPH, FDPH |
|  | FSPHB | Top bracket suspension kit, 304 Stainless Steel | FSPH |
| | FSPHWA | Top bracket wall/angle kit, 304 Stainless Steel | FSPH |

ACCESSORIES





Mounting Accessories

TECHNICAL

CHAIN AND CABLE HANGERS

| Chain and Cable Hangers | Cat. No. | Description | For Use With |
|---|------------------------------|---|---|
|  | LUNHK | Chain hanging (chain not included) | LU |
| | SSHK | Stainless Steel hanging kit (chain not included) | LU |
|  | CSHC | Chain hanging assembly includes two 24" lengths of chain and two hanger hooks. | CS, LCS, and CSR (Use KHC for fluorescent HO or VHO) |
| | KHC | Chain hanging assembly includes two 24" lengths of chain and two hanger hooks. | K and KL |
| | ICHC | Chain hanger assembly, #3 size double loop chain, 12'. | IC |
|  | GLH5 GLH10 GLH20 | Cable hangers, #2 size cable with loop-end, 5', 10', and 20' lengths, adjustable | All industrials |
| | LHVQM5 LHVQM10 LHVQM20 | Y-Fit Hook Cable Hangers, #2 size cable, 5', 10', and 20' lengths, adjustable | LHV and LHA |
| | CM24 CM48 | Single point mount cable with canopy kit, pair. (Feed and non-feed ends) 24" or 48" with barrel adjuster. | STP. Others may require field drilling of mounting holes. |

PENDANT/STEM MOUNTING ACCESSORIES

| Pendant/Stem Mounting | Cat. No. | Description | For Use With |
|---|----------|--|--|
|  | HUBK | Stem hanging kit consists of two die cast hubs, two "O" rings and locknuts. Hubs are threaded for 1/2" pipe. Housings must be drilled to install hubs. | FNPV, LU, FNPS, FNPH, FDPH |
|  | S18D | Double canopy (2) 18" stems | All 4' RO and PT |
|  | SB3 | Stem hanger adaptor bracket for 3-lamp surface mounted units. Reduces total number of mounting points required. | MWW 3-lamp EWW 3-lamp AWW 3-lamp WCW 3-lamp (Use for 3-Lamp fluorescent only; use S18, SS18, C18, S018 for LED and 2-Lamp or 4-Lamp fluorescent) |
|  | S18 | Swivel canopy, one 18" stem - all white finish, 8° swivel | Individual or continuous row mounting of most surface and industrial fixtures |
| | SS18 | Swivel canopy, one 18" stem - all white finish, 45° swivel | |
| | C18 | Swivel canopy only - all white finish, 8° swivel | |
| | S018 | One 18" stem only - all white finish | |