

## Products

- › [Index](#)
- › [Featured Products](#)
- › [Cross Reference](#)
- › [UPC Search](#)

## Product Datasheet

[Catalog Home](#)[Home Page](#)[Search](#)

## 3414 -- Straight Liquidtight Connector 3-1/2" Trade Size



### Product Specifications

<b>Family</b>	Liquidtight Conduit and Cord Connectors
<b>Fittings Classification</b>	Steel / Malleable Iron - Straight Connectors
<b>Sub Class</b>	Uninsulated
<b>Trade Size</b>	3-1/2"
<b>Standard Packaging</b>	Carton
<b>Ship Carton Length</b>	5.8125
<b>Ship Carton Width</b>	5.3125
<b>Ship Carton Height</b>	3.8125
<b>WT. PER HU.</b>	485.00
<b>Dimension A</b>	5-1/4"
<b>Dimension B</b>	1-1/8"
<b>Thread Spec. B</b>	3-1/2-8 NPT
<b>Dimension C</b>	3-3/4"
<b>Unit Carton Quantity</b>	1
<b>Ship Carton Quantity</b>	1
<b>UPC Number</b>	050169034149

### Applications

- For use in outdoor or indoor locations on flexible metallic liquidtight conduit and Type B flexible nonmetallic liquidtight conduit
- Use to positively bond the conduit to a box or enclosure
- RACO® liquidtight connectors are suitable for use in Class 1, Division 2; Class 2, Division 1 and 2; and Class 3, Division 1 and 2 hazardous locations

### Product Features

- Patented split gland-ring is designed to slip onto the conduit quickly and to grip the jacket of the conduit, speeding installation, assuring a perfect seal, and preventing pullouts
- All components are reusable -- RACO® liquidtight connectors may be easily disassembled and reused after years of service
- Sealing washer (included) provides a liquidtight seal when terminating the connector in a threadless opening
- Heavy duty locknut included with every RACO® liquidtight connector assures continuity of ground
- All metallic components are zinc electro plated for added corrosion protection
- Bodies - 3/8" to 1" Steel ; 1-1/4" to 4" Malleable Iron ; •Nuts - 3/8" to 1" Steel ; 1-1/4" to 4" Malleable Iron

### Compliances

UL CSA

