

Products

- › Index
- › Featured Products
- › Cross Reference
- › UPC Search

Product Datasheet

[Catalog Home](#) [Home Page](#)

[Search](#)

3518 -- Straight Liquidtight Connector 2" Trade Size Insulated



Product Specifications

Family	Liquidtight Conduit and Cord Connectors
Fittings Classification	Steel / Malleable Iron - Straight Connectors
Sub Class	Insulated
Trade Size	2"
Standard Packaging	Carton
Ship Carton Length	8.375
Ship Carton Width	7.5
Ship Carton Height	2.875
WT. PER HU.	146.71
Dimension A	3-1/2"
Dimension B	21/32"
Thread Spec. B	2-11-1/2 NPT
Dimension C	2-3/4"
Unit Carton Quantity	5
Ship Carton Quantity	5
UPC Number	050169035184

Applications

- For use in outdoor or indoor locations on flexible metallic liquidtight conduit and Type B flexible nonmetallic liquidtight conduit
- Use to positively bond the conduit to a box or enclosure
- RACO® liquidtight connectors are suitable for use in Class 1, Division 2; Class 2, Division 1 and 2; and Class 3, Division 1 and 2 hazardous locations

Product Features

- Patented split gland-ring is designed to slip onto the conduit quickly and to grip the jacket of the conduit, speeding

- installation, assuring a perfect seal, and preventing pullouts
- All components are reusable -- RACO® liquidtight connectors may be easily disassembled and reused after years of service
 - Sealing washer (included) provides a liquidtight seal when terminating the connector in a threadless opening
 - Heavy duty locknut included with every RACO® liquidtight connector assures continuity of ground
 - All metallic components are zinc electro plated for added corrosion protection
 - Bodies - 3/8" to 1" Steel ; 1-1/4" to 4" Malleable Iron ; •Nuts - 3/8" to 1" Steel ; 1-1/4" to 4" Malleable Iron

Compliances

UL CSA

