

## Products

- › [Index](#)
- › [Featured Products](#)
- › [Cross Reference](#)
- › [UPC Search](#)

## Product Datasheet

[Catalog Home](#)[Home Page](#)[Search](#)

## 3702-6 -- Cord Grip Connector 1/2" Trade Size .500 - .600



### Product Specifications

|                                |                                                 |
|--------------------------------|-------------------------------------------------|
| <b>Family</b>                  | Liquidtight Conduit and Cord Connectors         |
| <b>Fittings Classification</b> | Steel / Malleable Iron Strain Relief Connectors |
| <b>Sub Class</b>               | 1/2 inch Hubs Form 2                            |
| <b>Trade Size</b>              | 1/2"                                            |
| <b>Cable Range</b>             | .500 - .600                                     |
| <b>Standard Packaging</b>      | Carton                                          |
| <b>Ship Carton Length</b>      | 6.25                                            |
| <b>Ship Carton Width</b>       | 4.5                                             |
| <b>Ship Carton Height</b>      | 4.25                                            |
| <b>WT. PER HU.</b>             | 15                                              |
| <b>Dimension A</b>             | 1-3/16"                                         |
| <b>Thread Spec. A</b>          | 1/2-14 NPT                                      |
| <b>Dimension B</b>             | 19/32"                                          |
| <b>Dimension C</b>             | 1-7/16"                                         |
| <b>Unit Carton Quantity</b>    | 25                                              |
| <b>Ship Carton Quantity</b>    | 25                                              |
| <b>UPC Number</b>              | 050169370261                                    |

### Applications

- For use in wet or dry locations to provide a liquidtight and strain relief termination for flexible cord and cable
- RACO® liquidtight strain relief cord connectors are suitable for use in Class 1, Division 2; Class 2, Division 1 and 2; and Class 3, Division 1 and 2 hazardous locations

### Product Features

- All steel/malleable construction provides mechanical strength
- Unique Neoprene grommet design -- grommet is forced up and around the cord when the nut is tightened for a positive liquidtight seal
- Washers have size range imprinted for identification -- eliminates misidentifying inventory
- Use RACO® locknuts and sealing washers to complete a liquidtight installation on a sheet metal box or panel
- All metallic components are zinc electro plated for corrosion protection
- Bodies - 3/8" to 1-1/2" Malleable Iron; Nuts - 3/8" to 1" Steel, 1-1/4" Malleable Iron

### Compliances

C/UL/US

