

# PS4-11-20WT

Square steel poles with welded tenon included for use with floodlights. Designed for ground mounting. Poles are stocked nationwide for quick shipment. Protective packaging ensures poles arrive at the job site good as new.

Color: Bronze

Weight: 138.0 lbs

## Lamp Info

Type: N/A  
Watts: 0W  
Shape/Size: N/A  
Base: N/A  
ANSI: N/A  
Hours: 0  
Lamp Lumens: 0  
Efficacy: N/A

## Ballast Info

Type: N/A  
120V: N/A  
208V: N/A  
240V: N/A  
277V: N/A  
Input Watts: 0W  
Efficiency: N/A

## Technical Specifications

### CSA Listed:

Suitable for wet locations.

### Shaft:

46,000 p.s.i. minimum yield.

### Hand Holes:

Reinforced with grounding lug and removable cover.

### Base Plates:

Slotted base plates 36,000 p.s.i.

### Shipping Protection:

All poles are shipped in individual corrugated cartons to prevent finish damage.

### Color:

Bronze powder coating.

### Tenon:

Welded 2 3/8" tenon included.

### Terms of Sale:

Pole Terms of Sale is available .

### Height:

20 FT.

### Gauge:

11

### Wall Thickness:



1/8".

### Shaft Size:

4".

### Hand Hole Dimensions:

3" x 5".



### Bolt Circle:

8-9".

### Base Dimension:

8".

### Weight:

138 lbs.

### Anchor Bolt:

Galvanized anchor bolts and galvanized hardware and anchor bolt template. All bolts have a 3" hook.

### Anchor Bolt Templates:

WARNING Template must be printed on 11" x 17" sheet for actual size. CHECK SCALE BEFORE USING. Templates shipped with anchor bolts and available .

### Pre-Shipped Anchor Bolts:

Bolts can be pre-shipped upon request for additional freight charge.

### MaxEPA's/Max Weights:

70MPH 8.3 ft\_/240 lb  
80MPH 5.6 ft\_/165 lb  
90MPH 3.6 ft\_/110 lb  
100MPH 2.2 ft\_/75 lb  
110MPH 1.0 ft\_/45 lb  
120MPH 0.2 ft\_/20 lb.